MULTITASKS

MTM

FAE multi-function head for tractors from 240 to 360 hp.


The MTM enables ground stabilization, milling of slabs of rock, crushing of stones, and milling of asphalt, down to a maximum operating depth of 16 in.
The compact size and excellent maneuverability enable the MTM to work on surfaces which are difficult to reach using self-powered vehicles. The variable-geometry crushing chamber guarantees excellent results in terms of breaking down material.
The volume of the chamber increases based on depth with a reduction in fuel consumption and an increase in operating speed. The Hardox wear-resistant counter blade and grid on the rear hood guarantee the desired granulometry of material processed.

240-360 hp

Depth 16 in

Variable displacement chamber






Side wear plates on the inner sides of the frame highly resistant to wear and tear, equalling less down time due to replacement



Rear access panel

Hardox® steel - Wear plates
these allow the machine to resist wear and tear and can be easily replaced as needed







Rear grid
the grid on the rear door helps define the size of the output materials

Displacement Chamber
this technological solution, witch is one of a kind in the industry, allows the ground to be penetrated with the rotor alone

MAIN OPTIONS



Extended 3 point linkage



Bolt-on chain's protection plates



Multiple tooth options



The **Water Spray System** (High Flow & FCS) has the dual function of cooling and mixing

STANDARD EQUIPMENT

Hydraulic front hood	Gearbox with freewheel
Hydraulic rear hood	PTO shaft (MTM/HP)
Interchangeable inner antiwear plates in Hardox®	Friction clutches
Enclosed machine body	PTO shaft with cam clutch (MTM)
Variable displacement chamber	Bolted-on rotor shafts (in forged steel)
Bolted grid on rear hood	Adjustable Hardox® counter-blade
Inside lateral protection	Adjustable skids
Protection chains	Dozing blades with spring system
Transmission with side gearbox	

OPTIONS

Extended 3 point linkage	Water spray system WSS High Flow
Multiple tooth options	FCS full control system
Hydraulic top link	IVT - CVT or creeper transmission mandatory

MODEL		MTM-200	MTM-225	MTM/HP-200	MTM/HP-225
	Engine (hp)	240-300	240-300	300-360	300-360
	PTO (rpm)	1000	1000	1000	1000
	Working width (in)	81	90	81	90
	Total width (in)	98	108	98	108
	Weight (lbs)	12897	13999	13007	14110
G/3	**Rotor diameter** (in)	37.0	37.0	37.0	37.0
G/3	**Working depth** (in) (Max. 1-Max. 2)	10-16	10-16	10-16	10-16
G/3	**No. teeth** type G/3+STC/3/FP+STC/FP	94+4+4	106+4+4	94+4+4	106+4+4
ROTOR R	**Rotor diameter** (in)	36.0	36.0	36.0	36.0
ROTOR R	**Working depth** (in) (Max. 1-Max. 2)	9-16	9-16	9-16	9-16
ROTOR R	**No. pickis/teeth** type R/65+R/65/HD+STC/3/FP+STC/FP	126+20+4+4	144+20+4+4	126+20+4+4	144+20+4+4

Max. 1: with rotor only Max. 2: maximum depth (maximum working depth depending on ground conditions).
This information refers to the machine equipped as standard. The technical data in this catalogue may be altered without prior notice.

ROTOR TYPE G



TOOTH G/3 (standard)



TOOTH G/3/HD (option)



ADAPTOR G/3 WITH PICK R/44 (option)

ROTOR TYPE R



PICK R/65 (standard)



PICK R/65/HD (option)



ADAPTOR R/65 WITH PICK R/44 (option)



TOOTH STC/FP (side scraper)



TOOTH STC/3/FP (side scraper)



PICK R/65/HD (side scraper)